



LENZI EGISTO®

Fabric Certificate: FLASH LE 17137b ff

Identification		Construction	
Reference name:	FLASH LE 17137b ff	weight:(± 5%)	620 field gr/sqm (ISO 3801)
Usable width cm.:	135 (± 2%)	weight:(± 5%)	837 grs./lin mt. (ISO 3801)
		Comp.:	51%PL TPE 49% PA

Performance

		Warp	Weft	Test Methods
Tear strength: (Newton , singler tear)		>228	>690	UNI EN ISO 13937-2
Tensile Strength: (Newton)		>1745	>1140	UNI EN ISO 13934-1
Extension : (Percentage)		68%	77%	
Seam Slippage (N):		>104	>91	UNI EN ISO 13936-1
Abrasion resistance: (nu Martindale)	Dry: >100.000 Wet: >100.000			UNI EN 13520 (12 kPa)
Pilling: (nu Martindale, after 51.200k revs)	absent			ISO 12947 (12kpa)

Note:

Please note that above mentioned datas are average figures. Results have been obtained by testing at FF S.r.l. laboratories in Vaiano, following tests and methods procedures as ISO, UNI etc, as stated. FF S.r.l. reserves the rights to change parameters with no previous notice. We recommend that any fabric has to be carefully evaluated on the basis of final employ. FF S.r.l. can not be responsible for a fabric used when its technical characteristics are not suitable for its end use.

FF S.r.l.

Registered Office: Via G. Di Vittorio, n. 39 - 59021 Vaiano (PO) Italy
Tel. +39 0574.946030 / 0574.946599 – Fax. +39 0574.946048
e-mail: lab.resp@lenziegisto.it – web: www.lenziegisto.it
VAT Number: 06270040485